



US009531379B2

(12) **United States Patent**
Dassanayake et al.

(10) **Patent No.:** **US 9,531,379 B2**
(45) **Date of Patent:** **Dec. 27, 2016**

(54) **PROXIMITY SWITCH ASSEMBLY HAVING
GROOVE BETWEEN ADJACENT
PROXIMITY SENSORS**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Ford Global Technologies, LLC,**
Dearborn, MI (US)

3,382,588 A 5/1968 Serrell et al.
3,544,804 A 12/1970 Gaumer et al.
(Continued)

(72) Inventors: **Mahendra Somasara Dassanayake,**
Bloomfield Hills, MI (US); **Pietro**
Buttolo, Dearborn Heights, MI (US);
Stuart C. Salter, White Lake, MI (US)

FOREIGN PATENT DOCUMENTS

DE 4024052 1/1992
EP 1152443 11/2001
(Continued)

(73) Assignee: **Ford Global Technologies, LLC,**
Dearborn, MI (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 226 days.

U.S. Appl. No. 14/635,140, filed Mar. 2, 2015, entitled "Proximity
Switch Having Wrong Touch Adaptive Learning and Method," (20
pages of specification and 7 pages of drawings) and Official Filing
Receipt (3 pages).

(21) Appl. No.: **14/314,364**

U.S. Appl. No. 14/661,325, filed Mar. 18, 2015, entitled "Proximity
Switch Assembly Having Haptic Feedback and Method," (31 pages
of specification and 15 pages of drawings) and Official Filing
Receipt (3 pages).

(22) Filed: **Jun. 25, 2014**

U.S. Appl. No. 14/689,324, filed Apr. 17, 2015, entitled "Proximity
Switch Assembly With Signal Drift Rejection and Method," (35
pages of specification and 17 pages of drawings) and Official Filing
Receipt (3 pages).

(65) **Prior Publication Data**

(Continued)

US 2014/0306724 A1 Oct. 16, 2014

Primary Examiner — Tung X Nguyen

Assistant Examiner — Dominic Hawkins

(74) *Attorney, Agent, or Firm* — Vichit Chea; Price
Heneveld LLP

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/284,659,
filed on May 22, 2014, which is a continuation-in-part
(Continued)

(57) **ABSTRACT**

(51) **Int. Cl.**
G01R 27/26 (2006.01)
H03K 17/955 (2006.01)

A proximity switch assembly and method for detecting
activation of a proximity switch assembly is provided. The
assembly includes a plurality of proximity switches each
having a proximity sensor providing a sense activation field
and control circuitry processing the activation field of each
proximity switch to sense activation. A pliable material
overlays the proximity sensors. The control circuitry moni-
tors the activation field and determines an activation of a
proximity switch based on a signal generated by the sensor
in relation to a threshold when a user's finger depresses the
pliable material. The pliable material may further include an
elevated portion and an air gap between the elevated portion
and the sensor.

(52) **U.S. Cl.**
CPC ... **H03K 17/955** (2013.01); **H03K 2217/94031**
(2013.01); **H03K 2217/94052** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G01R 27/2605; G01D 5/24; G01L 9/12
See application file for complete search history.

20 Claims, 24 Drawing Sheets

